



---

# Anti-Slip Decking Strip


## Short Description

---

Decking Strips are an ideal solution for walkways and pedestrian areas where prevention of slips, trips and falls are a priority. The slimline profile is designed to fix directly to the floor surface to dramatically improve surface grip. Made from high quality fibreglass with chamfered edges ensures longevity and maximum safety.

## Product Images

---



## Description

---

- Moulded fibreglass GRP decking strip, with chamfered edge to both edges.
- Robust construction to withstand heavy usage and harsh environments.
- Impregnated silica grit surface protects against delamination - a common problem with metal backed alternatives.
- Fire-retardant additives ensure excellent fire and heat resistance, conforming to ASTM E84.
- Overall 4mm thickness.
- Available in bespoke lengths up to 3m, with additional options of drilling and countersinking.

## Additional Information

### Specifications

<b>Wear Resistant</b>	Wear resistant surface to Level 3
<b>Slip Resistance</b>	Slip resistance Level 3
<b>Chemical Resistant</b>	Chemical resistant
<b>Flame Retardant</b>	Flame retardant
<b>Outdoor</b>	Suitable for outdoor use
<b>Dry Area</b>	Suitable for use in dry areas
<b>Grease Area</b>	Suitable for use in greasy areas
<b>Heavy Areas</b>	Suitable for use in heavy use areas
<b>Oil Area</b>	Suitable for use in oily and greasy areas
<b>Wet Area</b>	Suitable for use in wet areas

### Environment

<b>Dry Zone</b>	Dry Zone
<b>Wet Zone</b>	Wet Zone
<b>Oily/Greasy Zone</b>	Oily/Greasy Zone
<b>Chemical Zone</b>	Chemical Zone

### Tests

- Pendulum Test Value (PTV), Dry 82, Wet 76
- Ignitability, tested to EN ISO 9239-1: 2010
- Radiant panel test for floorings, tested to EN ISO 9239-1
- Anti-slip, tested to BS7976.2
- ASTM E84

## Product Options

---

Colour:	Black
	Yellow
Width:	50mm
	90mm
Length:	1m
	3m